

Solutions
for aggregate processing



PRIMARY

ICR-P Geminis

Power and versatility in primary crushing

GEMINIS

ROBUSTNESS FOR THE MOST DEMANDING PROJECTS

GEMINIS

**Robustness for the most
demanding projects**


Designed for high
performance with
minimal maintenance and
maximum durability.

PERFORMANCE
WITH MINIMAL
MAINTENANCE
AND MAXIMUM
DURABILITY

GEMINIS

Power and versatility
in primary crushing

ARJA



INPUT



up to
**650
mm**

Maximum
input size

OUTPUT



**0-140
mm**

Output Size
(First Pass)

ICR-P Geminis Precise rock size reduction



FEED OPENING

- Lined with cast steel for greater durability.
- Interchangeable components.
- Easy exterior access for quick maintenance.

SQUARE WITH HEEL


- Protects the mill housing as the anti-return plate adjusts due to wear.


ANTI-RETURN PLATE

- Keeps material inside the crushing chamber.
- Ensures smaller sizes move into the crushing chamber.

FEED RAMP

- Maximum feed size: 650 mm.
- Designed with an anti-rebound system.
- Minimizes wear or damage to hoppers and belts.





EASY ACCESS

Quick and easy access to the crushing chamber via four side doors.

TWO IMPACT PLATES

Perfect cubicity with two impact plates and standard hydraulic adjustment.

0-140 MM OUTPUT

First-pass output size: 0-140 mm.

650 MM INPUT

Maximum input size: 650 mm.



POSITIONING BARS

Blow bars with positioning system, utilizing 70% of the casting.

CERAMIC BARS

High-chrome blow bars and plates, also available in ceramic.

LIFTING SYSTEM

Easy replacement of bars and impact plates.

HIGH VERSATILITY

Highly versatile secondary impact crushers.


WEAR PARTS

Interchangeable consumable parts.

REINFORCED ROTOR

Oversized and reinforced rotor.

TECHNICAL DATA



IMPACT CRUSHER



	ICR-P Geminis 1209	ICR-P Geminis 1213
Dimensions (A x B x C) (cm)	A 3780 B 1965 C 2555	A 3950 B 2470 C 2460
Production (TPH)	200-250	300-350
Power (kW)	160-200	250-315
Weight (Kg)	14700	19600
Input Rock Size (mm)	885 x 1025 mm	885 x 1500 mm
Feed Size (mm)	0-650 mm	0-650 mm
Blow Bars (units)	8	12

ROTOR



	ICR-P Geminis 1209	ICR-P Geminis 1213
Diameter (mm)	1270	1270
Length (mm)	935	1400
Weight (Kg)	2566	3751
Bars (units)	8	12
Arms (units)	4	4

ABOUT

US

ARVA



+40
years

+1200
crushers sold

+45
countries

Over four decades serving the industry

Since 1982, ARJA has been a leader in the crushing and screening industry.



Our history is the foundation of our reputation: we manufacture and supply cutting-edge equipment to configure complete plants, providing comprehensive service from project conception to commissioning.

Our complete product range reflects our commitment to high-quality, customized solutions, incorporating the latest innovations in impact crushing.

We are a benchmark brand in Europe, with a global presence spanning over 30 countries, highlighting our ability to adapt and respond to the needs of an ever-evolving market.





Carretera Alamús, s/n
Els Alamús, Lleida, Spain.
Tel. +34 973 199 163
info@arja.com

GEM NITE